

Continue





Please follow these steps for a safe and successful installation: Before setting up your pool filter system, read all instructions carefully and refer to product data plates for further information. **\*\*WARNING\*\*:** This equipment operates with air in the circulation system. Proper use can prevent serious injury or property damage. Make sure to shut off the pump before servicing the unit and keep it out of reach of young children. Inspect the equipment thoroughly when receiving it and notify your dealer if you find any damage or missing parts. Verify that all components match the specifications. Install the unit on a solid foundation as close to the pool/spa as possible, keeping a distance of at least five feet (1.5M) away. Consideration should be taken for proper drainage, ventilation, and future maintenance. When selecting a pump, choose a self-priming model if the equipment will be placed above the water level. Consult with your dealer to determine the correct size and placement of the pump, considering friction losses and other associated equipment. For solvent weld connections, use rigid or flexible PVC pipe and ensure clean ends without flash caused by cutting operations. Use recommended adhesives, such as Pool-Tite 2000 or IPS Weld-On 705, following manufacturer instructions. A primer is also essential for superior bonding. When connecting threaded components, apply Teflon tape or equivalent to prevent leaks. Remember to follow all safety precautions and manufacturer guidelines during the installation process. The recommended plumbing connections should be made using pipe compounds that are compatible with the materials being used. However, other pipe compounds may cause damage to the threads. It's advised not to use silicone or petroleum-based compounds due to their potential to harm the system. When tightening the connections, it's essential to hand-tighten plus an additional 1/2 turn is sufficient to avoid over-tightening. Before preparing the sand filter, ensure that you follow these steps: Firstly, place a standpipe cover on the standpipe to prevent any sand from entering. The standpipe cover can be found in the miscellaneous parts bag or separately in the carton. In some cases, the filter may already have the standpipe cover installed and the diverter removed. Next, fill the tank approximately 1/2 full with water.

Swimming pool filter cleaning. Carvin pool sand filter manual. Pool cartridge filter cleaning. Carvin pool manual. Does charcoal filter chlorine. Carvin pool filter manual pdf. Carvin sherlock pool filter manual. Carvin pool pump manual. Carvin pool instructions. Do charcoal filters remove chlorine.